



## **OPERATION**

Version-02 Cal.NH3 Series (NH34A/35A/36A/37A/38A/39A)

NH34A NH35A Minute hand Minute hand Crown at normal position Crown at normal position Hour hand Hour hand Crown at first position Crown at first position Crown at Crown at second position second position Second hand Second hand



24 hour hand



## 1.How to set the time

- 1) Pull out the crown to the second click position.
- 2) Turn the crown to set hour and minute hands. (Check that AM / PM is set correctly)
- 3) Push the crown back into the normal position.

## 2.How to set the Date & Time difference

- 1) Pull out the crown to the first click position.
- 2) Turn the crown to left for date setting.
- 3) Turn the crown to right for day setting. (Cal.NH36A only)

\*Do not set the date between 9:00 P.M. and 4:00 A.M. as this will cause a malfunction.

- 4) Turn the crown to right for 24 hour hand setting. (Cal.NH34A only)
- 5) Push the crown back into the normal position.

## 3.To wind up the mainspring

- a) Manual winding (Rotate the crown clockwise at normal position)
  Fully wound up by turning the crown minimum 55 times. It will start to move naturally after shaking slightly.
- b) To wind up with winding machine.

Full wind up conditions (Reference information)

Rotary speed : 30 rpmOperating time : 60 minutes